

Printing date 12/06/2005

Reviewed on 12/06/2005

**1 Identification of substance**· Product details

- Trade name: **Platinum Transparent Flowing**
- Article number: 10726
- Application of the substance / the preparation Polyester resin adhesive
- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg  
Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de
- Information department: Laboratory

**2 Composition/Data on components**· Chemical characterization

- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 100-42-5	styrene	25-50%
EINECS: 202-851-5	Xn; R 10-20-36/38	
EU Number: 601-026-00-0		
CAS: 67-56-1	methanol	<1%
EINECS: 200-659-6	T, F; R 11-23/24/25-39/23/24/25	
EU Number: 603-001-00-X		
CAS: 38668-48-3	1,1'-(p-tolyimino)dipropan-2-ol	<1%
EINECS: 254-075-1	T; R 25-52/53	

- Additional information: For the wording of the listed risk phrases refer to section 16.

**3 Hazards identification**

- Hazard description: Xn Harmful
- Information pertaining to particular dangers for man and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
Flammable.  
Harmful by inhalation.  
Irritating to eyes and skin.
- Classification system: The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- NFPA ratings (scale 0 - 4) Health = 2  
Fire = 3  
Reactivity = 0
- HMIS-ratings (scale 0 - 4) Health = 2  
Fire = 3  
Reactivity = 0

**4 First aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- The following symptoms may occur: Headache

(Contd. on page 2)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2005

Reviewed on 12/06/2005

Trade name: **Platinum Transparent Flowing**

(Contd. of page 1)

Dizziness  
Dizziness**5 Fire fighting measures**

- Suitable extinguishing agents: CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards caused by the material, its products of combustion or resulting gases: In case of fire, the following can be released:  
Carbon monoxide (CO)  
Formation of toxic gases is possible during heating or in case of fire.
- Protective equipment: Mount respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**6 Accidental release measures**

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

**7 Handling and storage**

- Handling:
- Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.  
Store in cool, dry conditions in well sealed receptacles.

**8 Exposure controls and personal protection**

- Additional information about design of technical systems: No further data; see item 7.
- Components with limit values that require monitoring at the workplace: \_\_\_\_\_

**100-42-5 styrene**

PEL Short-term value: C 200,600\* ppm

Long-term value: 100 ppm

\*5-min peak in any 3 hrs

REL Short-term value: 425 mg/m<sup>3</sup>, 100 ppmLong-term value: 215 mg/m<sup>3</sup>, 50 ppmTLV Short-term value: 170 mg/m<sup>3</sup>, 40 ppmLong-term value: 85 mg/m<sup>3</sup>, 20 ppm

BEI

(Contd. on page 3)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2005

Reviewed on 12/06/2005

Trade name: **Platinum Transparent Flowing**

(Contd. of page 2)

**67-56-1 methanol**PEL 260 mg/m<sup>3</sup>, 200 ppmREL Short-term value: 325 mg/m<sup>3</sup>, 250 ppmLong-term value: 260 mg/m<sup>3</sup>, 200 ppm

Skin

TLV Short-term value: 328 mg/m<sup>3</sup>, 250 ppmLong-term value: 262 mg/m<sup>3</sup>, 200 ppm

Skin; BEI

- Additional information: The lists that were valid during the creation were used as basis.
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.  
Filter AX
- Protection of hands: Protective gloves
- Material of gloves: Fluorocarbon rubber (Viton)  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material: The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Tightly sealed goggles
- Body protection: Protective work clothing

**9 Physical and chemical properties**· General Information

Form: Fluid  
Color: Light yellow  
Odor: Specific type

· Change in condition

Melting point/Melting range: Undetermined.  
Boiling point/Boiling range: 145°C (293°F)

- Flash point: 31°C (88°F)
- Ignition temperature: 480°C (896°F)
- Auto igniting: Product is not selfigniting.
- Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- Explosion limits:
  - Lower: 1.2 Vol %
  - Upper: 8.9 Vol %
- Vapor pressure at 20°C (68°F): 6 hPa (5 mm Hg)
- Density at 20°C (68°F): ~ 1.12 g/cm<sup>3</sup>
- Solubility in / Miscibility with Water: Not miscible or difficult to mix.
- Viscosity:
  - Dynamic at 20°C (68°F): 900 - 1300 mPas (Viscot. DK3)

**10 Stability and reactivity**

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Dangerous reactions Exothermic polymerization.

(Contd. on page 4)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2005

Reviewed on 12/06/2005

Trade name: **Platinum Transparent Flowing**

(Contd. of page 3)

· Dangerous products of decomposition:

Reacts with peroxides and other radical forming substances.

No dangerous decomposition products known.

## 11 Toxicological information

· Acute toxicity:  
 · LD/LC50 values that are relevant for classification:

### 100-42-5 styrene

Oral LD50 5000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

· Primary irritant effect:

· on the skin:

Irritant to skin and mucous membranes.

· on the eye:

Irritating effect.

· Sensitization:

No sensitizing effects known.

· Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful  
Irritant

## 12 Ecological information

· General notes:

Do not allow product to reach ground water, water course or sewage system.  
 Water hazard class 2 (Self-assessment): hazardous for water

## 13 Disposal considerations

· Product:

· Recommendation:

Must be specially treated adhering to official regulations.  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation:

Disposal must be made according to official regulations.  
 Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

## 14 Transport information

· DOT regulations:

· Hazard class:

3

· Identification number:

UN3269

· Packing group:

III

· Proper shipping name (technical name): POLYESTER RESIN KIT

· Label

3

· Land transport ADR/RID (cross-border):

· ADR/RID class:

3 (F1) Flammable liquids

· Danger code (Kemler):

30

· UN-Number:

3269

· Packaging group:

III

· Description of goods:

3269 POLYESTER RESIN KIT

· Remarks:

Without hardener component: no dangerous goods &lt; 450 l

· Maritime transport IMDG:

· IMDG Class:

3

· UN Number:

3269

· Label

3

· Packaging group:

III

· EMS Number:

F-E,S-E

· Marine pollutant:

No

· Proper shipping name:

POLYESTER RESIN KIT

(Contd. on page 5)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2005

Reviewed on 12/06/2005

Trade name: **Platinum Transparent Flowing**

(Contd. of page 4)

- Remarks: Without hardener component: no dangerous goods < 30 l
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 3
- UN/ID Number: 3269
- Label 3
- Packaging group: III
- Propper shipping name: POLYESTER RESIN KIT
- Remarks: Without hardener component: 3/III UN 1866 Resin Solution

## \* 15 Regulations

- Sara
- Section 355 (extremely hazardous substances):  
None of the ingredient is listed.
- Section 313 (Specific toxic chemical listings):  
100-42-5 styrene  
  
85-44-9 phthalic anhydride  
  
67-56-1 methanol
- TSCA (Toxic Substances Control Act):  
All ingredients are listed.
- Proposition 65
- Chemicals known to cause cancer:  
None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for females:  
None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males:  
None of the ingredients is listed.
- Chemicals known to cause developmental toxicity:  
None of the ingredients is listed.
- Cancerogenity categories
- EPA (Environmental Protection Agency)  
None of the ingredients is listed.
- IARC (International Agency for Research on Cancer)  
100-42-5 styrene: 2B
- NTP (National Toxicology Program)  
None of the ingredients is listed.
- TLV (Threshold Limit Value established by ACGIH)  
100-42-5 styrene: A4  
  
85-44-9 phthalic anhydride: A4
- MAK (German Maximum Workplace Concentration)  
100-42-5 styrene: 5
- NIOSH-Ca (National Institute for Occupational Safety and Health)  
None of the ingredients is listed.
- OSHA-Ca (Occupational Safety & Health Administration)  
None of the ingredients is listed.
- Product related hazard informations: The product has been classified and marked in accordance with directives on hazardous materials.
- Hazard symbols: Xn Harmful
- Hazard-determining components of labelling: styrene
- Risk phrases: Flammable.  
Harmful by inhalation.  
Irritating to eyes and skin.
- Safety phrases: Keep out of the reach of children.  
Do not breathe fumes

(Contd. on page 6)

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 12/06/2005

Reviewed on 12/06/2005

**Trade name: Platinum Transparent Flowing**

(Contd. of page 5)

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point

Wear suitable gloves.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

· National regulations:· Water hazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS:

Laboratory

· Contact:

Dieter Zimmermann

· \* Data compared to the previous version altered.